



**LEGEND**

- A. INSIDE WIDTH \_\_\_\_\_
- B. OUTSIDE WIDTH \_\_\_\_\_
- C. LEFT WALL SPACE \_\_\_\_\_
- D. RIGHT WALL SPACE \_\_\_\_\_
- E. INSIDE LENGTH \_\_\_\_\_
- F. TOP OF WINDOW FRAME TO BOTTOM OF APRON \_\_\_\_\_
- G. TOP OF WINDOW FRAME TO 1" ABOVE FLOOR \_\_\_\_\_
- H. TOP OF WINDOW FRAME TO TOP OF CURTAIN ROD \_\_\_\_\_
- I. WINDOW DEPTH \_\_\_\_\_

**INSIDE MOUNT** Width (A) \_\_\_\_\_ Length (E) \_\_\_\_\_

**OUTSIDE MOUNT**

Width is \_\_\_\_\_ + \_\_\_\_\_ + \_\_\_\_\_ = \_\_\_\_\_ total width  
B C D

Length is \_\_\_\_\_ + \_\_\_\_\_ = \_\_\_\_\_ total length  
G H

Puddle Length is \_\_\_\_\_ + \_\_\_\_\_ + 20" = \_\_\_\_\_ total puddle length  
G H

**MEASURING GUIDELINES**

1. Always measure in inches.
2. Always use a metal measuring tape.
3. Mount curtain rod 4" or more above window frame (H).
4. Mount curtain rod to ensure it extends 3 – 5 inches on each side of the window frame to make sure curtains cover the width of the apron and sill (C & D).
5. With decorative rods hung by rings, start measuring from the bottom of the ring (ring length listed on packaging).
6. Measurement to the floor or carpet should be 1" above the floor or carpet.
7. **Inside Mount:** width is (A) and length is (E). (I) lets you know if you have enough depth for an inside mounted curtains with a tension rod. You need at least ½ inch.
8. **Outside Mount:** Width is determined by adding (B) + (C) + (D). For example, 25" + 5" + 5" = 35". Length is determined by adding (G) + (H). For example, 80" + 4" = 84".
9. You can add inches to (G) if you want your curtain or drape to "puddle" on the floor. Add 20" to (G) to cause the curtain to "puddle" on the floor. For example, (G) + (H) + 20" =

Return